Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

Owner Name: Kentwood Park  Address: 2302 Makin Rd. Bidg B    Item Pinone:   Item	Inspection Date: 10/25/2024						
Address: 2302 Maki Rd. Bidg B  City: Plant City, FL  Zip: 33563  Work Phone:  County: Hillsbrorugh  Rough Folion:    Substitute   Policy #:							
City: Plant City, FL  County: Hillsborrough  County: Hillsborrough  County: Hillsborrough  County: Hillsborrough  Policy #:  Year of Home:  1987  # of Stories: Two  Email:  NOTE: Any documentation used in validating the compliance or existence of each construction or mitigation attribute must accompany this form. At least one photograph must accompany this form to validate each attribute marked in questions 3 though 7. The insurer may ask additional questions regarding the mitigated feature(s) verified on this form.  1. Building Code: Was the structure built in compliance with the Florida Building Code (FBC 2001 or later) OR for homes located in the HYHZ (Miami-Dade or Broward counties). South Florida Building Code (FBC 2001 or later) OR for homes located in the HYHZ (Miami-Dade or Broward counties). South Florida Building Code (FBC 2001 or later) OR for homes located in the HYHZ (Miami-Dade or Broward counties). South Florida Building Code (FBC 2001 or later) OR for homes located in the HYHZ (Miami-Dade or Broward counties). South Florida Building Code (FBC 2001 or later) OR for homes located in the HYHZ (Miami-Dade or Broward counties). South Florida Building Code (FBC 2001 or later) OR for homes located in the HYHZ (Miami-Dade Droil and Intervention). The Properties of the Properties							
Country: Hillsborough    Rostroace Company:   Policy #:	<u> </u>						
Insurance Company:  Year of Home:  1987    # of Stories: Two   Email:  NOTE: Any documentation used in validating the compliance or existence of each construction or mitigation attribute must accompany this form. At least one photograph must accompany this form to validate each attribute marked in questions 3 though 7. The insurer may ask additional questions regarding the mitigated feature(s) verified on this form.  1. Building Code: Was the structure built in compliance with the Florida Building Code (FBC-94)?    A. Built in compliance with the FBC: Year Built   For homes built in 2002/2003 provide a permit application with a date after 31/2002. Studingle Permit Application Date ⊕ ₱ FBC-94. Year Built   For homes built in 1994, 1995, and 1996 provide a permit application with a date after 91/1994: Building Permit Application Date ⊕ Provide Permit Provided Permit Permit Provided Permit Provided Permit Permit Permit Permit Provided Permit Permit Permit Permit Permit Permit Permit Permit Permi		Zip: 33563					
NOTE: Any documentation used in validating the compliance or existence of each construction or mitigation attribute must accompany this form. At least one photograph must accompany this form to validate each attribute marked in questions 3 though 7. The insurer may ask additional questions regarding the mitigated feature(s) verified on this form.  1. Building Code: Was the structure built in compliance with the Florida Building Code (FBC 2001 or later) OR for homes located in the HVHZ (Miami-Dade or Broward counties), South Florida Building Code (FBC 2001 or later) OR for homes located in the HVHZ (Miami-Dade or Broward counties), South Florida Building Code (FBC 2001 or later) OR for homes located in the HVHZ (Miami-Dade or Broward counties), South Florida Building Code (FBC 2001 or later) OR for homes located in the HVHZ (Miami-Dade or Broward counties), South Florida Building Code (FBC 2001 or later) OR for homes located in the HVHZ (Miami-Dade or Broward counties), South Florida Building Code (FBC 2001 or later) OR FBC. 94)?  A. Built in compliance with the FBC: Year Built For homes built in 2002/2003 provide a permit application with a date after 91/1994; Building Permit Application Date owners with a provide a permit application with a date after 91/1994; Building Permit Application Date owners with a provide a permit application with a date after 91/1994; Building Permit Application date OR FBC/MDC Product Approval mumber OR Year of Original Installation/Replacement OR indicate that no information was available to verify compliance for each roof covering dentified.  2. Roof Covering Type:  2. Roof Covering Type:  2. Roof Covering Type:  3. Roof Developed Type Permit Applications Developed Product Approval Bisting current at time of installation OR have a roofing permit application after 91/1994 and before 31/12002 OR the roof is original and built in 2004 or later.  3. Roof Developed Type States of the Application after 91/1994 and before 31/12002 OR the roof is original and built in 1997 or late	<del>-</del>						
NOTE: Any documentation used in validating the compliance or existence of each construction or mitigation attribute must accompany this form. At least one photograph must accompany this form to validate each attribute marked in questions 3 though 7. The insurer may ask additional questions regarding the mitigated feature(s) verified on this form.  1. Building Code: Was the structure built in compliance with the Florida Building Code (FBC 2001 or later) OR for homes located in the HVHZ (Miami-Dade or Broward counties). South Florida Building Code (FBC 2001 or later) OR for homes located in the HVHZ (Miami-Dade or Broward counties). South Florida Building Code (FBC 2001 or later) OR for homes located in the HVHZ (Miami-Dade or Broward counties). South Florida Building Code (FBC 2001 or later) OR 700 or later). The for homes built in 2002/2003 provide a permit application with a date after 9/11/94/8. Building permit Application Date ORDEROYYYY	· ·						
accompany this form. At least one photograph must accompany this form to validate each attribute marked in questions 3 though 7. The insurer may ask additional questions regarding the mitigated feature(s) verified on this form.  1. Building Code: Was the structure built in compliance with the Florida Building Code (FBC 2001 or later) OR for homes located in the HVHZ (Mismi-Dade or Broward counties), South Florida Building Code (FBC 2001 or later) OR for homes located in the HVHZ (Mismi-Dade or Broward counties), South Florida Building Code (FBC 2010 or later) OR for homes built in compliance with the FBC: Year Built	Year of Home: 1987	Year of Home: # of Stories: Two Email:					
the HVHZ (Miami-Dade or Broward counties), South Florida Building Code (SFBC-94)?  A. Built in compliance with the FBC: Year Built	accompany this form. At least one pl	notograph must accompa	ny this form to val	idate each attribute marked	l in questions 3		
2.1 Roof Covering Type: Permit Application Date Product Approval # Year of Original Installation or Replacement Provided for Compiliance Product Approval # 2024  □ 1. Asphalit Fiberglass Shingle O7/25/2024 2024  □ 2. ConcreteClay Tile	A. Built in compliance with the a date after 3/1/2002: Building B. For the HVHZ Only: Built in provide a permit application with the conference of the confe	d counties), South Florida FBC: Year Built Permit Application Date (w) In compliance with the SFB th a date after 9/1/1994: Buther requirements of Answerering types in use. Provide	Building Code (SFE For homes build For homes building Permit Applied and For homes building Permit Applied	alt in 2002/2003 provide a period in 2002/2003 provide a period in 19 ication Date (MM/DD/YYYY)/_ on date OR FBC/MDC Production	mit application with 94, 1995, and 1996/		
2. Concrete/Clay Tile  3. Metal  4. Built Up  5. Membrane  6. Other  B. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Product Approval listing current at time of installation OR have a roofing permit application date on or after 3/1/02 OR the roof is original and built in 2004 or later.  B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later.  C. One or more roof coverings do not meet the requirements of Answer "A" or "B".  D. No roof coverings meet the requirements of Answer "A" or "B".  A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the fieldOR- Batten decking supporting wood shakes or wood shinglesOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the fieldOR- Any system of screws, nails, adhesives, other deck fastening system of screws, nails, adhesives, other deck fastening system of truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the fieldOR- Any system of screws, nails, adhesives, other deck fastening system of truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the fieldOR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width)OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent					Provided for		
□ 3. Metal □ 4. Built Up □ 5. Membrane □ 6. Other □ A. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Product Approval listing current at time of installation OR have a roofing permit application date on or after 3/1/02 OR the roof is original and built in 2004 or later. □ B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later. □ C. One or more roof coverings do not meet the requirements of Answer "A" or "B". □ D. No roof coverings meet the requirements of Answer "A" or "B". □ A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the fieldOR- Batten decking supporting wood shakes or wood shinglesOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below. □ B. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the fieldOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails spaced a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf. □ C. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the fieldOR- Dennesional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width)OR- Any system of screws, nails, adhesives, other deck fastening system or truss/	1. Asphalt/Fiberglass Shingle	07/25/2024		2024			
□ 4. Built Up □ 5. Membrane □ 6. Other □ A. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Product Approval listing current at time of installation OR have a roofing permit application date on or after 3/1/02 OR the roof is original and built in 2004 or later. □ B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later. □ C. One or more roof coverings do not meet the requirements of Answer "A" or "B". □ D. No roof coverings meet the requirements of Answer "A" or "B". □ No roof coverings meet the roof the VIZ inches o.c.) by 8d common nails spaced a maximum of 12" inches in the field. "OR- Any system of screws, nails, adhe	2. Concrete/Clay Tile						
□ 4. Built Up □ 5. Membrane □ 6. Other □ A. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Product Approval listing current at time of installation OR have a roofing permit application date on or after 3/1/02 OR the roof is original and built in 2004 or later. □ B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later. □ C. One or more roof coverings do not meet the requirements of Answer "A" or "B". □ D. No roof coverings meet the requirements of Answer "A" or "B". □ D. No roof coverings meet the requirements of Answer "A" or "B". □ A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the fieldOR- Batten decking supporting wood shakes or wood shinglesOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter (spaced a maximum of 24" inches o.c.) by 8d common nails spaced a maximum of 12" inches in the fieldOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails spaced a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf. □ C. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the fieldOR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width)OR-Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent	3. Metal	/ /					
A. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Product Approval listing current at time of installation OR have a roofing permit application date on or after 3/1/02 OR the roof is original and built in 2004 or later.  B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later.  C. One or more roof coverings do not meet the requirements of Answer "A" or "B".  D. No roof coverings meet the requirements of Answer "A" or "B".  3. Roof Deck Attachment: What is the weakest form of roof deck attachment?  A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the fieldOR- Batten decking supporting wood shakes or wood shinglesOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the fieldOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter (spaced a maximum of 12" inches in the field or has a mean uplift resistance of at least 103 psf.  C. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the fieldOR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width)OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent	4. Built Up						
A. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Product Approval listing current at time of installation OR have a roofing permit application date on or after 3/1/02 OR the roof is original and built in 2004 or later.  B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later.  C. One or more roof coverings do not meet the requirements of Answer "A" or "B".  D. No roof coverings meet the requirements of Answer "A" or "B".  A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the fieldOR- Batten decking supporting wood shakes or wood shinglesOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below.  B. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the fieldOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails spaced a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.  C. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the fieldOR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width)OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent	_						
A. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Product Approval listing current at time of installation OR have a roofing permit application date on or after 3/1/02 OR the roof is original and built in 2004 or later.  B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later.  C. One or more roof coverings do not meet the requirements of Answer "A" or "B".  D. No roof coverings meet the requirements of Answer "A" or "B".  A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the fieldOR- Batten decking supporting wood shakes or wood shinglesOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below.  B. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the fieldOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails spaced a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.  C. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the fieldOR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width)OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent					$\vdash$		
Inspectors michael 110porty Madress	installation OR have a roofing profing permit application after C. One or more roof coverings of D. No roof coverings meet the profing permit application after C. One or more roof coverings of D. No roof coverings meet the profine of D. No roof Deck Attachment: What is the profine of D. No roof Deck Attachment: What is the profine of D. No roof Deck Attachment: What is the profine of D. No roof Deck Attachment: What is the profine of Deck Attachment: What is the profi	permit application date on ami-Dade Product Approv 9/1/1994 and before 3/1/2 do not meet the requirement requirements of Answer "A reweakest form of roof de ard (OSB) roof sheathing at 6" along the edge and 12 crews, nails, adhesives, other dor Options B or C belong with a minimum thickness field or has a mean uplift in a gwith a minimum thickness and spaced a maximum of the structure of the st	or after 3/1/02 OR the roal listing current at 002 OR the roof is onts of Answer "A" of A" or "B".  ck attachment?  attached to the roof is attached to the roof of attached to the roof of attached fastening spow.  css of 7/16"inch attached in the ison to have an expension of at least assort of 12" inches in the ison of 6" inches in the first board if each boarding system or truss/	truss/rafter (spaced a maximum batten decking supporting waystem or truss/rafter spacing to ched to the roof truss/rafter (sfieldOR- Any system of screquivalent or greater resistance 103 psf. ched to the roof truss/rafter (sfieldOR- Dimensional lumber of is equal to or less than 6 in the roof instance in the roof is equal to or less than 6 in the roof is or the roof is equal to or less than 6 in the roof is or the roof is equal to or less than 6 in the roof is or the roof is equal to or less than 6 in the roof is or the roof is equal to or less than 6 in the roof is or the roof is equal to or less than 6 in the roof is or the roof is or the roof is equal to or less than 6 in the roof is or the roof	a 2004 or later.  The HVHZ only) a later.  The HVHZ only a l		
	Inspectors initials w 110perty At	141 600			<del></del>		

\*This verification form is valid for up to five (5) years provided no material changes have been made to the structure. OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155 Page 1 of 4

		or gr 182 <sub>1</sub>		esistan	uce than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at leas
	$\neg$	-	•	ed Co	oncrete Roof Deck.
r	$\neg$		ther:		
Γ	7	F. U	nknow	n or u	nidentified.
	Π,	G. N	lo attic	acces	S.
	5 fee	et of	the insi	de or	ment: What is the <u>WEAKEST</u> roof to wall connection? (Do not include attachment of hip/valley jacks within outside corner of the roof in determination of WEAKEST type)
		A. I	oe Nail	Trı	ass/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached top plate of the wall, or
				Me	tal connectors that do not meet the minimal conditions or requirements of B, C, or D
I	Mini	imal	conditi	— ions t	o qualify for categories B, C, or D. All visible metal connectors are:
_			<b>√</b>	_	cured to truss/rafter with a minimum of three (3) nails, and
_	7		✓	the	ached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from blocking or truss/rafter <b>and</b> blocked no more than 1.5" of the truss/rafter, <b>and</b> free of visible severe rosion.
١		B. C	Clips	7	
			<b>✓</b>	╡ .	tal connectors that do not wrap over the top of the truss/rafter, or
_	_		L	pos	stal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the natition requirements of C or D, but is secured with a minimum of 3 nails.
		C. S	ingle W		tal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with
					nimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.
		D. I	Oouble '		
	_			bea bea	tal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond am, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with hinimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or
_	_				tal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on h sides, and is secured to the top plate with a minimum of three nails on each side.
L	[ ]	E. S	tructura	ıl	Anchor bolts structurally connected or reinforced concrete roof.
L	_  1	F. O	ther: _		
Ļ	_				nidentified
L		H. N	lo attic	acces	S
					at is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).
L		A. F	Iip Roo	f	Hip roof with no other roof shapes greater than 10% of the total roof system perimeter.  Total length of non-hip features: feet; Total roof system perimeter: feet
		B. F	lat Roo	of	Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft
•		C. C	Other Ro	oof	Any roof that does not qualify as either (A) or (B) above.
6. <u>1</u>		A. S si d B. N	WR (all heathing welling To SWR	lso ca g or for g from R.	sistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) lled Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the pam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the water intrusion in the event of roof covering loss.
L		C. U	nknow	n or u	andetermined.
Íner	nect:	ore I	nitial	M	Property Address 2302 Maki Rd. Bldg B
.113 <u>}</u> *ТL	ic v	orifi.	nation 4		is valid for up to five (5) years provided no material changes have been made to the structure or

<sup>\*</sup>This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

7. Opening Protection: What is the weakest form of wind borne debris protection installed on the structure? First, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

-	ening Protection Level Chart an "X" in each row to identify all forms of protection in use for each	Glazed Openings			Non-Glazed Openings		
openi form	ng type. Check only one answer below (A thru X), based on the weakest of protection (lowest row) for any of the Glazed openings and indicate eakest form of protection (lowest row) for Non-Glazed openings.	Windows or Entry Doors	Garage Doors	Skylights	Glass Block	Entry Doors	Garage Doors
N/A	Not Applicable- there are no openings of this type on the structure		Х	Х	Х		Х
Α	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)						
В	Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)						
С	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007						
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance						
	Opening Protection products that appear to be A or B but are not verified						
N	Other protective coverings that cannot be identified as A, B, or C						
Х	No Windborne Debris Protection	Х				Х	
	<ul> <li>Miami-Dade County PA 201, 202, and 203</li> <li>Florida Building Code Testing Application Standard (TAS) 200</li> <li>American Society for Testing and Materials (ASTM) E 1886 200</li> <li>Southern Standards Technical Document (SSTD) 12</li> <li>For Skylights Only: ASTM E 1886 and ASTM E 1996</li> </ul>	· · · · · · · · · · · · · · · · · · ·					
Г	• For Garage Doors Only: ANSI/DASMA 115  A.1 All Non-Glazed openings classified as A in the table above, or no Non-C	Hazed openi	nge eviet				
	A.2 One or More Non-Glazed openings classified as Level D in the table above  X in the table above	-	-	d openings	classified	l as Leve	1 B, C, N, o
	1.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X i	n the table a	bove				
o <sub>l</sub>	Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb I benings are protected, at a minimum, with impact resistant coverings the product approval system of the State of Florida or Miami-Dade or "Cyclic Pressure and Large Missile Impact" (Level B in the table at ASTM E 1886 and ASTM E 1996 (Large Missile – 4.5 lb.)	or products County and	s listed as	windborr	ne debris	protect	ion device
	• SSTD 12 (Large Missile – 4 lb. to 8 lb.)						
	<ul> <li>For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large</li> </ul>						
	B.1 All Non-Glazed openings classified as A or B in the table above, or no N						
L	B.2 One or More Non-Glazed openings classified as Level D in the table about in the table above	ove, and no N	Ion-Glaze	d openings	classified	l as Leve	1 C, N, or 2
	B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the	e table abov	e				
	Exterior Opening Protection- Wood Structural Panels meeting twood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2					are co	vered wi
	C.1 All Non-Glazed openings classified as A, B, or C in the table above, or r.						
	C.2 One or More Non-Glazed openings classified as Level D in the table about the table above				classified	l as Leve	l N or X in

C.3 One or More Non-Glazed openings is classified as Level N or X in the table above

Inspectors Initials Property Address 2302 Maki Rd. Bldg B

<sup>\*</sup>This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

N. Exterior Opening Protection (unverified shutter s					
protective coverings not meeting the requirements of A with no documentation of compliance (Level N in the ta		or systems that appear to meet Answer "A" or "B"			
N.1 All Non-Glazed openings classified as Level A, B, C, or N in the table above, or no Non-Glazed openings exist					
N.2 One or More Non-Glazed openings classified as Level table above					
N.3 One or More Non-Glazed openings is classified as Lev	al V in the table above				
		11 137 1 11 1			
X. None or Some Glazed Openings One or more Glaz	ed openings classified	and Level X in the table above.			
MITIGATION INSPECTIONS MUST E Section 627.711(2), Florida Statutes, prov	ides a listing of indivi	duals who may sign this form.			
Qualified Inspector Name: Richard Murphy	License Type:	License or Certificate #: 60			
Inspection Company: Murphy's Law Home Inspections, Inc		Phone: 813-228-6631			
Qualified Inspector – I hold an active license as a	: (check one)				
Home inspector licensed under Section 468.8314, Florida Statut training approved by the Construction Industry Licensing Board	es who has completed th				
☐ Building code inspector certified under Section 468.607, Florida	Statutes.				
☐ General, building or residential contractor licensed under Section	n 489.111, Florida Statut	es.			
☐ Professional engineer licensed under Section 471.015, Florida S	tatutes.				
☐ Professional architect licensed under Section 481.213, Florida S	tatutes.				
Any other individual or entity recognized by the insurer as posses verification form pursuant to Section 627.711(2), Florida Statute		ifications to properly complete a uniform mitigation			
Individuals other than licensed contractors licensed under	Section 489.111, Flor	ida Statutes, or professional engineer licensed			
under Section 471.015, Florida Statues, must inspect the st					
<u>Licensees under s.471.015 or s.489.111 may authorize a dir</u> experience to conduct a mitigation verification inspection.	ect employee wno po	ssesses the requisite skill, knowledge, and			
Diahand Mumbu	1 7	anni dala taman dan an di			
(print name)	ing i personally peri-	ormed the inspection or (licensed			
contractors and professional engineers only) I had my emplo		perform the inspection name of inspector)			
and I agree to be responsible for his/her work.	/	mine of mispector)			
Qualified Inspector Signature: Date: 10/25/2024					
An individual or entity who knowingly or through gross negligence provides a false or fraudulent mitigation verification form is					
subject to investigation by the Florida Division of Insurance Fraud and may be subject to administrative action by the					
appropriate licensing agency or to criminal prosecution. (Section 627.711(4)-(7), Florida Statutes) The Qualified Inspector who					
certifies this form shall be directly liable for the misconduction.	et of employees as if t	he authorized mitigation inspector personally			
<b>Homeowner to complete:</b> I certify that the named Qualifie residence identified on this form and that proof of identification					
Signature: Date:					
An individual or entity who knowingly provides or utters a obtain or receive a discount on an insurance premium to w of the first degree. (Section 627.711(7), Florida Statutes)					
The definitions on this form are for inspection purposes on as offering protection from hurricanes.	ly and cannot be use	d to certify any product or construction feature			
Inspectors Initials Property Address 2302 Maki Ro	I. Bldg B				
*This verification form is valid for up to five (5) years proving account on the form	ided no material cha	nges have been made to the structure or			

inaccuracies found on the form.



## City of Plant City 302 West Reynolds Street Plant City, FL 33563

## PERMIT NUMBER

0724-04806

Issued Date: 7/25/2024

Permit Type: Roof Comm

Property Number	Street Address		
205010.0210	2302 MAKI RD, E, Plant City FL 33563-7115		
Floor Elevation: Flood Zone:	Jurisdiction Applicant Information		
Owner Information			
Name: HTR PROPERTIES LLC	Name: Krzysztof Szostek		
Address: 1242 CONCORD HUNT DR, BRENTWOOD, TN	Phone:		
Contractor Information			
Name:	Permit Trades Name:		
Address:	Permit Tradesman Lic #:		
Phone:	Termit madesman Lie $\pi$ .		
Building Information			
Proposed Use:	Total Sq. Ft:		
Construction Type:	Living Area Sq. Ft:		
Number of Stories:			
Estimated Cost of Construction: \$9,875.00			

## Project Description:

\*UNITS 5-8\* Remove existing and install new OC Shingles FL#10674.R19, Peel and Stick Underlayment FL#46297.R2, 25SQS, 5/12

Fees	
HCRF/DCA SURCHARGE - Roof	\$2.00
DBPR/BCAI - Roof	\$2.25
Building - NOC (Notice of Commencement) fee	\$5.00
Building - Re-roof	\$150.00

<sup>\*\*\*</sup>AN ADDITIONAL \$5 NOC FEE MAY APPLY\*\*\*

The permit holder shall agree to comply with all applicable laws regulating the work. Having received a copy of this document and understanding that it is the permit holder's responsibility to inform this office of any change of contractor by completing and submitting a change of contractor form if necessary. I further understand that all inspection requests are to be made by me or my agent.

Ray Pat

Date: 7/25/2024

Signature of Permit Approver

ANY PERMIT ISSUED EXPIRES SIX (6) MONTHS AFTER ISSUANCE IF NO INSPECTIONS HAVE BEEN MADE

4
\$159.25









Kentwood Park

2302 Maki Rd. Bldg B

Plant City, FL

33563









Kentwood Park

2302 Maki Rd. Bldg B

Plant City, FL

33563